

CLEAR FOCUS JetVue FILM

Exterior Adhesive Mount InkJet Product Specifications

Flexible Vinyl

Removable Adhesive

Black/White flexible 8-mil vinyl film with removable acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors or other transparent surfaces
--------------	--

MAKEUP	Black/White PVC laminate, inkjet-receptive coated, with pressure-sensitive adhesive coating with release liner
--------	--

OPEN AREA	50% (approximately)
-----------	---------------------

VINYL THICKNESS	.008" (.2 mm)
-----------------	---------------

RELEASE LINER THICKNESS	.007" (.17 mm)
-------------------------	----------------

ADHESIVE THICKNESS	.001" (.02 mm)
--------------------	----------------

PERFORATION SIZE	.080" (2.0 mm) hole diameter
------------------	------------------------------

DIMENSIONAL STABILITY	Good
-----------------------	------

MINIMUM APPLICATION TEMPERATURE	40° F (4° C)
---------------------------------	--------------

SERVICE TEMPERATURE RANGE	0° F to 140° F (-17° C to 60° C)
---------------------------	----------------------------------

EXPECTED ADHESIVE VINYL LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
---	--

EXPECTED IMAGE LIFETIME	Varies according to ink type, use of clear coat or overlamine, and conditions under which image is displayed. Conduct test prior to production.
-------------------------	---

WATER RESISTANCE	Not recommended where immersed in water
------------------	---

HUMIDITY RESISTANCE	Fair
---------------------	------

STORAGE STABILITY	One-year shelf life when stored at 70° F (21° C) and 50% relative humidity
-------------------	--

COLORS AVAILABLE	White/black laminate (white on one side, black on the other)
------------------	--

PRINTING	Pigment-, dye- or water-based inkjet inks recommended. Print image on non-
----------	--
